

GALLENKAMP GENFUGE 13R



G A L L E N K A M P



OVERVIEW

Gallenkamp high speed personal centrifuge Genfuge 13R provide excellent centrifugal effect and is easy to be used with high reliability and safety.

- Maximum speed 15000rpm
- Maximum capacity 24×1.5/2.0ml, 16×5ml
- Temperature range -10~40

NEOFUGE

- Genfuge laboratory centrifuge is equipped with a precise electronic imbalance detection system.
- It uses a patented lid-lock system for safety.
- It comes with a LCD display which indicates the speed, RCF, time, temperature, acceleration, braking rates and error message.
- Genfuge 13R laboratory centrifuge is refrigerated by a CFC-free unit with a temperature control range of -10 to 40.
- It provides rotor pre-cooling function.
- Fixed angle rotor #1303 is offered as a standard accessory.
- Five autoclavable(121, 20min) ultra-duralumin airtight rotors are available.
- Genfuge 13R offers automatic rotor identification function.
- It will give alarms if there is any abnormality.
- Genfuge 13R provide a maximum speed of 13800rpm and a maximum RCF of 17458×g..



Code	Description	Capacity
7BZ-GENFUGE13-EX	High speed centrifuge	24x1.5/2.0 ml
7BZ-GENFUGE13R-EX	High speed refrigerated centrifuge	24x1.5/2.0 ml

Model	13	13R
Cooling	No	Yes
Temp control range 0C	N/a	-10C-40C
Max speed RPM	300-13800 rpm	300-13800 can be extended to 15000rpm
Max RCF (g)	17460g	17459 g can be extended to 20627g
Dimensions WxHxD (mm)	370x230x250	525x300x350
Weight (Kg)	18	47

Model	13	13R
Code	7BZ-NEOFUGE13-EX	7BZ-NEOFUGE13R-EX
Description	High speed centrifuge	High speed refrigerated centrifuge
Capacity	24x1.5/2.0 ml	24x1.5/2.0 ml

Beacon House
Nuffield Road
Cambridge
CB4 1TF
United Kingdom

Tel: +44(0)1223 727 100
Email: sales@fistreem.co.uk



G A L L E N K A M P

www.gallenkamp-labs.com